

# “Carriage Series”

## Custom Stain Grade Garage Doors

### Standard Specifications

#### Base Door

- 1” Hem/Fir core, mechanically assembled, with machined profiled “Shiplap” joints.
- ¼” marine grade Meranti plywood skins both sides, adhered with staples and waterproof adhesive.
- Full cavity semi-rigid fiberglass insulation.
- Preservative prime painted finish to all surfaces unless specified otherwise.
- Base door thickness, 1 ½”. Overall finished door thickness, 2 5/8”.

#### Exterior Overlay ( Unfinished)

- 7/16” x 4” “A” and better clear Tongue and Groove “V” joint Western Red Cedar.
- Adhered with premium construction adhesive and blind brad nailed to frame.
- Continuous grain through full door height.
- Other materials are available at an extra charge.

#### Exterior Trim Out ( Unfinished)

- 1” x 6” “A” and better clear S4S Western Red Cedar.
- Adhered with premium construction adhesive.
- Countersunk screws through to core and screw holes filled with ½” hardwood plugs.
- Continuous grain through full door height.
- Other materials are available at an extra charge.

#### Glazing

- 3mil clear glass with cedar grilles standard.
- ½” thermal sealed units available at an extra charge.
- Textures, tempered, or tinted glass also available
- True Divided Lite glazing available at an extra charge.
- Simulated Divided Lite glazing available at an extra charge

#### Hardware (If included)

- 2” heavy gauge track with 15” curve radius, 12” radius and LHR also available.
- Commercial quality hinges, rollers and hardware.
- Heavy duty torsion springs.

#### Weather strip kits ( If included)

- Arctic grade u-shaped bottom weather strip with rigid P.V.C retainer.
- Wood with vinyl insert perimeter weather strip