

“Estate Series”

Classic Panel Style Garage Doors

Standard Specifications

Base Door

- 1” Hem/Fir core, mechanically assembled, with machined profiled “Shiplap” joints.
- ¼” marine grade Meranti plywood skins both sides, adhered with staples and waterproof adhesive.
- Full cavity semi-rigid fiberglass insulation.
- Preservative prime painted finish to all surfaces unless specified otherwise.
- Base door thickness, 1 ½”. Overall finished door thickness, 2 5/8”.

Exterior Overlay (Unfinished)

- ¾” raised or flat laminated, clear Cedar panels
- Floating construction unless pinning required for specific models.
- Paint grade Medex, Fir, African Mahogany and Alder are also available.

Exterior Trim Out (Unfinished)

- 5/8” x 5 ½” “A” and better clear precision machined profiled Western Red Cedar.
- Adhered with premium construction adhesive.
- Adhered with waterproof construction adhesive and brad nails.
- Continuous grain through full door height.
- Paint grade Medex, Fir, African Mahogany and Alder are also available.

Glazing

- 3mil clear glass with cedar grilles standard.
- ½” thermal sealed units available at an extra charge.
- Textures, tempered, or tinted glass also available
- True Divided Lite glazing available at an extra charge.
- Simulated Divided Lite glazing available at an extra charge

Hardware (If included)

- 2” heavy gauge track with 15” curve radius, 12” radius and LHR also available.
- Commercial quality hinges, rollers and hardware.
- Heavy duty torsion springs.

Weather strip kits (If included)

- Arctic grade u-shaped bottom weather strip with rigid P.V.C retainer.
- Wood with vinyl insert perimeter weather strip

Visit us @ www.equaldoor.com